MOSFET – Dual P-Channel POWERTRENCH®

-20 V, -2.6 A, 142 mΩ

FDME1023PZT



UDFN6 1.6×1.6 0.5P
(MicroFET™ 1.6×1.6 Thin)
CASE 517DW

Description

This device is designed specifically as a single package solution for the battery charges switch in cellular handset and other ultra−portable applications. It features two independent P−Channel MOSFETs with low on−state resistance for minimum conduction losses. When connected in the typical common source configuration, bi−directional current flow is possible.

The MicroFET 1.6×1.6 **Thin** package offers exceptional thermal performance for it's physical size and is well suited to switching and linear mode applications.

Features

- Max $R_{DS(on)}$ = 142 mΩ at V_{GS} = −4.5 V, I_D = −2.3 A
- Max $R_{DS(on)}$ = 213 mΩ at V_{GS} = −2.5 V, I_D = −1.8 A
- Max $R_{DS(on)}$ = 331 mΩ at V_{GS} = −1.8 V, I_D = −1.5 A
- Max $R_{DS(on)}$ = 530 mΩ at V_{GS} = −1.5 V, I_D = −1.2 A
- Low Profile: 0.55 mm Maximum in the New Package MicroFET 1.6 x 1.6 **Thin**
- HBM ESD Protection Level > 1600 V (Note 3)
- This Device is Pb−Free, Halide Free and RoHS Compliant

Typical Applications

- Load Switch
- Battery Charging
- Battery Disconnect Switch

ELECTRICAL CONNECTION



Dual P−Channel MOSFET
(Top View)

MARKING DIAGRAM



&Z = Assembly Plant Code
&2 = 2−Digit Date Code (Year and Week)
&K = 2−Digit Lot Run Code
2T = Specific Device Code

ORDERING INFORMATION

See detailed ordering and shipping information on page 6 of this data sheet.

ABSOLUTE MAXIMUM RATINGS (T_A = 25°C unless otherwise noted)

Symbol	Parameter		Value	Unit
V_{DS}	Drain to Source Voltage		−20	V
V_{GS}	Gate to Source Voltage		±8	V
I_D	Drain Current – Continuous (Note 1a) – Pulsed	T_A = 25°C	 −2.6 −6	A
P_D	Power Dissipation for Single Operation – (Note 1a) – (Note 1b)	 T_A = 25°C T_A = 25°C	 1.4 0.6	W
T_J, T_{STG}	Operating and Storage Junction Temperature Range		−55 to +150	°C

Stresses exceeding those listed in the Maximum Ratings table may damage the device. If any of these limits are exceeded, device functionality should not be assumed, damage may occur and reliability may be affected.

DISCONTINUED
THIS DEVICE IS NOT RECOMMENDED FOR NEW DESIGN
PLEASE CONTACT YOUR onsemi
REPRESENTATIVE FOR INFORMATION

THERMAL CHARACTERISTICS

Symbol	Parameter	Value	Unit
$R_{\theta JA}$	Thermal Resistance, Junction to Ambient (Single Operation) (Note 1a)	90	°C/W
$R_{\theta JA}$	Thermal Resistance, Junction to Ambient (Single Operation) (Note 1b)	195	

ELECTRICAL CHARACTERISTICS T_A = 25°C unless otherwise noted

Symbol	Parameter	Test Conditions	Min	Typ	Max	Units
Off Characteristics						
BV_{DSS}	Drain to Source Breakdown Voltage	I_D = −250 μA, V_{GS} = 0 V	−20	–	–	V
$\frac{\Delta BV_{DSS}}{\Delta T_J}$	Breakdown Voltage Temperature Coefficient	I_D = −250 μA, referenced to 25°C	–	−12	–	mV/°C
I_{DSS}	Zero Gate Voltage Drain Current	V_{DS} = −16 V, V_{GS} = 0 V	–	–	−1	μA
I_{GSS}	Gate to Source Leakage Current	V_{GS} = ±8 V, V_{DS} = 0 V	–	–	±10	μA
On Characteristics						
$V_{GS(th)}$	Gate to Source Threshold Voltage	V_{GS} = V_{DS}, I_D = −250 μA	−0.4	−0.6	−1.0	V
$\frac{\Delta V_{GS(th)}}{\Delta T_J}$	Gate to Source Threshold Voltage Temperature Coefficient	I_D = −250 μA, referenced to 25°C	–	2	–	mV/°C
$R_{DS(on)}$	Drain to Source On Resistance	V_{GS} = −4.5 V, I_D = −2.3 A	–	95	142	mΩ
		V_{GS} = −2.5 V, I_D = −1.8 A	–	120	213	
		V_{GS} = −1.8 V, I_D = −1.5 A	–	150	331	
		V_{GS} = −1.5 V, I_D = −1.2 A	–	190	530	mΩ
		V_{GS} = −4.5 V, I_D = −2.3 A, T_J = 125°C	–	128	190	mΩ
g_{FS}	Forward Transconductance	V_{DS} = −4.5 V, I_D = −2.3 A	–	7	–	S
Dynamic Characteristics						
C_{iss}	Input Capacitance	V_{DS} = −10 V, V_{GS} = 0 V, f =1 MHz	–	305	405	pF
C_{oss}	Output Capacitance		–	55	75	pF
C_{rss}	Reverse Transfer Capacitance		–	50	75	pF
Switching Characteristics						
$t_{d(on)}$	Turn−On Delay Time	V_{DD} = −10 V, I_D = −1 A, V_{GS} = −4.5 V, R_{GEN} = 6 Ω	–	4.7	10	ns
t_r	Rise Time		–	4.8	10	ns
$t_{d(off)}$	Turn−Off Delay Time		–	33	53	ns
t_f	Fall Time		–	16	29	ns
Q_g	Total Gate Charge	V_{DD} = −10 V, I_D = −2.3 A, V_{GS} = −4.5 V	–	5.5	7.7	nC
Q_{gs}	Gate to Source Gate Charge		–	0.6	–	nC
Q_{gd}	Gate to Drain “Miller” Charge		–	1.4	–	nC
Drain−Source Diode Characteristics						
V_{SD}	Source to Drain Diode Forward Voltage	V_{GS} = 0 V, I_S = −0.9 A (Note 2)	–	−0.8	−1.2	V
t_{rr}	Reverse Recovery Time	I_F = −2.3 A, di/dt = 100 A/μs	–	16	29	ns
Q_{rr}	Reverse Recovery Charge		–	4.4	10	nC

Product parametric performance is indicated in the Electrical Characteristics for the listed test conditions, unless otherwise noted. Product performance may not be indicated by the Electrical Characteristics if operated under different conditions.

DISCONTINUED
THIS DEVICE IS NOT RECOMMENDED FOR NEW DESIGN
PLEASE CONTACT YOUR onsemi
REPRESENTATIVE FOR INFORMATION

NOTES:

1. $R_{\theta JA}$ is determined with the device mounted on a 1 in^2 pad 2 oz copper pad on a 1.5 x 1.5 in. board of FR−4 material. $R_{\theta JC}$ is guaranteed by design while $R_{\theta JA}$ is determined by the user's board design.



a. 90°C/W when mounted on a 1 in^2 pad of 2 oz copper



b. 195°C/W when mounted on a minimum pad of 2 oz copper

2. Pulse Test : Pulse Width < 300 μs, Duty Cycle < 2.0%
3. The diode connected between gate and source serves only as protection against ESD. No gate overvoltage rating is implied.

DISCONTINUED
THIS DEVICE IS NOT RECOMMENDED FOR NEW DESIGN
PLEASE CONTACT YOUR onsemi
REPRESENTATIVE FOR INFORMATION

TYPICAL CHARACTERISTICS (T_J = 25°C unless otherwise noted)



Figure 1. On Region Characteristics



Figure 2. Normalized On−Resistance vs. Drain Current and Gate Voltage



Figure 3. Normalized On Resistance vs. Junction Temperature



Figure 4. On−Resistance vs. Gate to Source Voltage



Figure 5. Transfer Characteristics



Figure 6. Source to Drain Diode Forward Voltage vs. Source Current

DISCONTINUED
THIS DEVICE IS NOT RECOMMENDED FOR NEW DESIGN
PLEASE CONTACT YOUR onsemi
REPRESENTATIVE FOR INFORMATION

TYPICAL CHARACTERISTICS (T_J = 25°C unless otherwise noted) (continued)



Figure 8. Gate Charge Characteristics



Figure 9. Capacitance vs. Drain to Source Voltage



Figure 7. Forward Bias Safe Operating Area



Figure 10. Gate Leakage Current vs. Gate to Source Voltage



Figure 11. Single Pulse Maximum Power Dissipation

DISCONTINUED
THIS DEVICE IS NOT RECOMMENDED FOR NEW DESIGN
PLEASE CONTACT YOUR onsemi REPRESENTATIVE FOR INFORMATION

TYPICAL CHARACTERISTICS (T_J = 25°C unless otherwise noted) (continued)



Figure 12. Junction−to−Ambient Transient Thermal Response Curve

DISCONTINUED
THIS DEVICE IS NOT RECOMMENDED FOR NEW DESIGN
PLEASE CONTACT YOUR onsemi
REPRESENTATIVE FOR INFORMATION

PACKAGE MARKING AND ORDERING INFORMATION

Device	Device Marking	Package Type	Reel Size	Tape Width	Shipping†
FDME1023PZT	2T	UDFN6 1.6×1.6 0.5P (MicroFET 1.6×1.6 **Thin**) (Pb−Free/Halide Free)	7”	8 mm	5000 / Tape & Reel

†For information on tape and reel specifications, including part orientation and tape sizes, please refer to our Tape and Reel Packaging Specifications Brochure, BRD8011/D.

POWERTRENCH is a registered trademark of Semiconductor Components Industries, LLC dba “**onsemi**” or its affiliates and/or subsidiaries in the United States and/or other countries.
MicroFET is a trademark of Semiconductor Components Industries, LLC dba “**onsemi**” or its affiliates and/or subsidiaries in the United States and/or other countries.

UDFN6 1.6x1.6, 0.5P
CASE 517DW
ISSUE O

DATE 31 OCT 2016





RECOMMENDED
LAND PATTERN





NOTES:

A. PACKAGE DOES NOT CONFORM TO ANY JEDEC STANDARD.
B. DIMENSIONS ARE IN MILLIMETERS.
C. DIMENSIONS AND TOLERANCES PER ASME Y14.5M, 2009.
D. LAND PATTERN RECOMMENDATION IS EXISTING INDUSTRY LAND PATTERN.

DOCUMENT NUMBER:	**98AON13701G**	Electronic versions are uncontrolled except when accessed directly from the Document Repository. Printed versions are uncontrolled except when stamped "CONTROLLED COPY" in red.
DESCRIPTION:	**UDFN6 1.6x1.6, 0.5P**	**PAGE 1 OF 1**

onsemi and onsemi are trademarks of Semiconductor Components Industries, LLC dba **onsemi** or its subsidiaries in the United States and/or other countries. **onsemi** reserves the right to make changes without further notice to any products herein. **onsemi** makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does **onsemi** assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. **onsemi** does not convey any license under its patent rights nor the rights of others.

onsemi, ONSEMI , and other names, marks, and brands are registered and/or common law trademarks of Semiconductor Components Industries, LLC dba "**onsemi**" or its affiliates and/or subsidiaries in the United States and/or other countries. **onsemi** owns the rights to a number of patents, trademarks, copyrights, trade secrets, and other intellectual property. A listing of **onsemi**'s product/patent coverage may be accessed at www.onsemi.com/site/pdf/Patent−Marking.pdf. **onsemi** reserves the right to make changes at any time to any products or information herein, without notice. The information herein is provided "as−is" and **onsemi** makes no warranty, representation or guarantee regarding the accuracy of the information, product features, availability, functionality, or suitability of its products for any particular purpose, nor does **onsemi** assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. Buyer is responsible for its products and applications using **onsemi** products, including compliance with all laws, regulations and safety requirements or standards, regardless of any support or applications information provided by **onsemi**. "Typical" parameters which may be provided in **onsemi** data sheets and/or specifications can and do vary in different applications and actual performance may vary over time. All operating parameters, including "Typicals" must be validated for each customer application by customer's technical experts. **onsemi** does not convey any license under any of its intellectual property rights nor the rights of others. **onsemi** products are not designed, intended, or authorized for use as a critical component in life support systems or any FDA Class 3 medical devices or medical devices with a same or similar classification in a foreign jurisdiction or any devices intended for implantation in the human body. Should Buyer purchase or use **onsemi** products for any such unintended or unauthorized application, Buyer shall indemnify and hold **onsemi** and its officers, employees, subsidiaries, affiliates, and distributors harmless against all claims, costs, damages, and expenses, and reasonable attorney fees arising out of, directly or indirectly, any claim of personal injury or death associated with such unintended or unauthorized use, even if such claim alleges that **onsemi** was negligent regarding the design or manufacture of the part. **onsemi** is an Equal Opportunity/Affirmative Action Employer. This literature is subject to all applicable copyright laws and is not for resale in any manner.

ADDITIONAL INFORMATION

TECHNICAL PUBLICATIONS:
Technical Library: www.onsemi.com/design/resources/technical−documentation
onsemi Website: www.onsemi.com

ONLINE SUPPORT: www.onsemi.com/support
For additional information, please contact your local Sales Representative at
www.onsemi.com/support/sales