

Dual P-Channel Power MOSFET

FEATURES

- 1.8V drive
- Pb-free plating
- RoHS compliant
- Halogen-free


APPLICATIONS

- Power management
- Load switch


KEY PERFORMANCE PARAMETERS		
PARAMETER	VALUE	UNIT
V_{DS}	-20	V
$R_{DS(on)}$ (max)	$V_{GS} = -4.5V$	140
	$V_{GS} = -2.5V$	200
	$V_{GS} = -1.8V$	300
Q_g	5.2	nC



SOT-26



Block Diagram



Dual P-Channel MOSFET

Note: MSL 1 (Moisture Sensitivity Level) per J-STD-020

ABSOLUTE MAXIMUM RATINGS ($T_A = 25^\circ\text{C}$ unless otherwise noted)			
PARAMETER	SYMBOL	LIMIT	UNIT
Drain-Source Voltage	V_{DS}	-20	V
Gate-Source Voltage	V_{GS}	± 8	V
Continuous Drain Current	I_D	-2.2	A
Pulsed Drain Current (Note 1)	I_{DM}	-8.8	A
Total Power Dissipation	P_D	0.97	W
		0.6	
Operating Junction and Storage Temperature Range	T_J, T_{STG}	- 55 to +150	$^\circ\text{C}$

THERMAL PERFORMANCE			
PARAMETER	SYMBOL	LIMIT	UNIT
Junction to Ambient Thermal Resistance (Note 2)	$R_{\theta JA}$	128	$^\circ\text{C/W}$

Notes:

1. Pulse Width $\leq 100\mu\text{s}$.
2. Device on a PCB FR4 with 1 in² (single layer, 2 oz thickness) copper area for drain connection.

ELECTRICAL SPECIFICATIONS (T _A = 25°C unless otherwise noted)						
PARAMETER	CONDITIONS	SYMBOL	MIN	TYP	MAX	UNIT
Static (Note 3)						
Drain-Source Breakdown Voltage	V _{GS} = 0V, I _D = -250μA	BV _{DSS}	-20	--	--	V
Gate Threshold Voltage	V _{DS} = V _{GS} , I _D = -250μA	V _{GS(TH)}	-0.45	-0.63	-0.95	V
Gate Body Leakage	V _{GS} = ±8V, V _{DS} = 0V	I _{GSS}	--	--	±100	nA
Zero Gate Voltage Drain Current	V _{DS} = -16V, V _{GS} = 0V	I _{DSS}	--	--	-1	μA
Drain-Source On-State Resistance	V _{GS} = -4.5V, I _D = -2.2A	R _{DS(on)}	--	31	140	mΩ
	V _{GS} = -2.5V, I _D = -1.8A		--	43	200	
	V _{GS} = -1.8V, I _D = -1.3A		--	60	300	
Forward Transconductance	V _{DS} = -10V, I _D = -0.6A	g _{fs}	--	5.4	--	S
Dynamic (Note 4)						
Total Gate Charge	V _{DS} = -10V, I _D = -2.2A, V _{GS} = -4.5V	Q _g	--	5.2	--	nC
Gate-Source Charge		Q _{gs}	--	0.8	--	
Gate-Drain Charge		Q _{gd}	--	1	--	
Input Capacitance	V _{DS} = -10V, V _{GS} = 0V, f = 1.0MHz	C _{iss}	--	469	--	pF
Output Capacitance		C _{oss}	--	77	--	
Reverse Transfer Capacitance		C _{rss}	--	68	--	
Switching (Note 5)						
Turn-On Delay Time	V _{DD} = -10V, R _G = 3.3Ω, I _D = -2.2A, V _{GS} = -4.5V	t _{d(on)}	--	6.6	--	ns
Turn-On Rise Time		t _r	--	42	--	
Turn-Off Delay Time		t _{d(off)}	--	36	--	
Turn-Off Fall Time		t _f	--	33	--	
Source-Drain Diode						
Forward Voltage (Note 3)	I _S = -2.2A, V _{GS} = 0V	V _{SD}	--	-0.7	-1.2	V

Notes:

- Pulse test: Pulse Width $\leq 300\mu s$, duty cycle $\leq 2\%$.
- Defined by design. Not subject to production test.
- Switching time is essentially independent of operating temperature.


ORDERING INFORMATION

ORDERING CODE	PACKAGE	PACKING
TSM3911DCX6 RFG	SOT-26	3kpcs / 7" Reel


CHARACTERISTICS CURVES

($T_A = 25^\circ\text{C}$ unless otherwise noted)


Output Characteristics




Transfer Characteristics




On-Resistance vs. Drain Current




Gate-Source Voltage vs. Gate Charge



On-Resistance vs. Junction Temperature




On-Resistance vs. Gate-Source Voltage




CHARACTERISTICS CURVES

($T_A = 25^\circ\text{C}$ unless otherwise noted)


Capacitance vs. Drain-Source Voltage




BV_{DSS} vs. Junction Temperature




Maximum Safe Operating Area, Junction-to-Ambient



Source-Drain Diode Forward Current vs. Voltage






Normalized Thermal Transient Impedance, Junction-to-Ambient






CHARACTERISTICS CURVES

($T_A = 25^\circ\text{C}$ unless otherwise noted)



PACKAGE OUTLINE DIMENSIONS (Unit: Millimeters)

SOT-26



SUGGESTED PAD LAYOUT

DOT
MARKING,
PIN #1 ID

MARKING DIAGRAM

- 1D = Device marking
Y = Year Code
M = Month Code for Halogen Free Product
(O=Jan, P=Feb, Q=Mar, R=Apr, S=May, T=Jun, U=Jul, V=Aug, W=Sep, X=Oct, Y=Nov, Z=Dec)
L = Lot Code

NOTES: UNLESS OTHERWISE SPECIFIED

- ALL DIMENSIONS ARE IN MILLIMETERS.
- DIMENSIONING AND TOLERANCING PER ASME Y14.5M-1994.
- PACKAGE OUTLINE REFERENCE: JEDEC MO-178, VARIATION AB.
- MOLDED PLASTIC BODY DIMENSIONS DO NOT INCLUDE MOLD FLASH, PROTRUSIONS OR GATE BURRS.
- DWG NO. REF: HQ2SD07-SOT26-027 REV A.

Notice

Specifications of the products displayed herein are subject to change without notice. TSC or anyone on its behalf, assumes no responsibility or liability for any errors or inaccuracies.

Purchasers are solely responsible for the choice, selection, and use of TSC products and TSC assumes no liability for application assistance or the design of Purchasers' products.

Information contained herein is intended to provide a product description only. No license, express or implied, to any intellectual property rights is granted by this document. Except as provided in TSC's terms and conditions of sale for such products, TSC assumes no liability whatsoever, and disclaims any express or implied warranty, relating to sale and/or use of TSC products including liability or warranties relating to fitness for a particular purpose, merchantability, or infringement of any patent, copyright, or other intellectual property right.

The products shown herein are not designed for use in medical, life-saving, or life-sustaining applications. Customers using or selling these products for use in such applications do so at their own risk and agree to fully indemnify TSC for any damages resulting from such improper use or sale.