ON Semiconductor

Is Now

To learn more about onsemi™, please visit our website at
www.onsemi.com

onsemi and onsemi and other names, marks, and brands are registered and/or common law trademarks of Semiconductor Components Industries, LLC dba "**onsemi**" or its affiliates and/or subsidiaries in the United States and/or other countries. **onsemi** owns the rights to a number of patents, trademarks, copyrights, trade secrets, and other intellectual property. A listing of **onsemi** product/patent coverage may be accessed at www.onsemi.com/site/pdf/Patent-Marking.pdf. **onsemi** reserves the right to make changes at any time to any products or information herein, without notice. The information herein is provided "as-is" and **onsemi** makes no warranty, representation or guarantee regarding the accuracy of the information, product features, availability, functionality, or suitability of its products for any particular purpose, nor does **onsemi** assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. Buyer is responsible for its products and applications using **onsemi** products, including compliance with all laws, regulations and safety requirements or standards, regardless of any support or applications information provided by **onsemi**. "Typical" parameters which may be provided in **onsemi** data sheets and/or specifications can and do vary in different applications and actual performance may vary over time. All operating parameters, including "Typicals" must be validated for each customer application by customer's technical experts. **onsemi** does not convey any license under any of its intellectual property rights nor the rights of others. **onsemi** products are not designed, intended, or authorized for use as a critical component in life support systems or any FDA Class 3 medical devices or medical devices with a same or similar classification in a foreign jurisdiction or any devices intended for implantation in the human body. Should Buyer purchase or use **onsemi** products for any such unintended or unauthorized application, Buyer shall indemnify and hold **onsemi** and its officers, employees, subsidiaries, affiliates, and distributors harmless against all claims, costs, damages, and expenses, and reasonable attorney fees arising out of, directly or indirectly, any claim of personal injury or death associated with such unintended or unauthorized use, even if such claim alleges that **onsemi** was negligent regarding the design or manufacture of the part. **onsemi** is an Equal Opportunity/Affirmative Action Employer. This literature is subject to all applicable copyright laws and is not for resale in any manner. Other names and brands may be claimed as the property of others.

ON Semiconductor®

FDD3510H

Dual N & P-Channel PowerTrench® MOSFET
N-Channel: 80V, 13.9A, 80mΩ P-Channel: -80V, -9.4A, 190mΩ

Features

Q1: N-Channel

- Max $r_{DS(on)}$ = 80mΩ at V_{GS} = 10V, I_D = 4.3A
- Max $r_{DS(on)}$ = 88mΩ at V_{GS} = 6V, I_D = 4.1A

Q2: P-Channel

- Max $r_{DS(on)}$ = 190mΩ at V_{GS} = -10V, I_D = -2.8A
- Max $r_{DS(on)}$ = 224mΩ at V_{GS} = -4.5V, I_D = -2.6A
- 100% UIL Tested
- RoHS Compliant

General Description

These dual N and P- Channel enhancement mode Power MOSFETs are produced using ON Semiconductor's advanced PowerTrench® process that has been especially tailored to minimize on -state resistance and yet maintain superior switching performance.

Applications

- Inverter
- H-Bridge



Dual DPAK 4L



N-Channel P-Channel

MOSFET Maximum Ratings T_C = 25°C unless otherwise noted

Symbol	Parameter			Q1	Q2	Units
V_{DS}	Drain to Source Voltage			80	-80	V
V_{GS}	Gate to Source Voltage			±20	±20	V
I_D	Drain Current - Continuous	T_C = 25°C		13.9	-9.4	A
	- Continuous	T_A = 25°C		4.3	-2.8	
	- Pulsed			20	-10	
P_D	Power Dissipation for Single Operation	T_C = 25°C	(Note 1)	35	32	W
		T_A = 25°C	(Note 1a)	3.1		
		T_A = 25°C	(Note 1b)	1.3		
E_{AS}	Single Pulse Avalanche Energy		(Note 3)	37	54	mJ
T_J, T_{STG}	Operating and Storage Junction Temperature Range			-55 to +150		°C

Thermal Characteristics

$R_{\theta JC}$	Thermal Resistance, Junction to Case, Single Operation for Q1	(Note 1)	3.5	°C/W
$R_{\theta JC}$	Thermal Resistance, Junction to Case, Single Operation for Q2	(Note 1)	3.9	

Package Marking and Ordering Information

Device Marking	Device	Package	Reel Size	Tape Width	Quantity
FDD3510H	FDD3510H	TO-252-4L	13"	16mm	2500 units

©2008 Semiconductor Components Industries, LLC.

Electrical Characteristics T_J = 25°C unless otherwise noted

Symbol	Parameter	Test Conditions	Type	Min	Typ	Max	Units
Off Characteristics							
BV_{DSS}	Drain to Source Breakdown Voltage	I_D =250μA, V_{GS} = 0V I_D = -250μA, V_{GS} = 0V	Q1 Q2	80 -80			V
$\frac{\Delta BV_{DSS}}{\Delta T_J}$	Breakdown Voltage Temperature Coefficient	I_D = 250μA, referenced to 25°C I_D = -250μA, referenced to 25°C	Q1 Q2		84 -67	mV	/°C
I_{DSS}	Zero Gate Voltage Drain Current	V_{DS} = 64V, V_{GS} = 0V V_{DS} = -64V, V_{GS} = 0V	Q1 Q2			1 -1	μA
I_{GSS}	Gate to Source Leakage Current	V_{GS} = ±20V, V_{DS} = 0V	Q1 Q2			±100 ±100	nA nA
On Characteristics							
$V_{GS(th)}$	Gate to Source Threshold Voltage	V_{GS} = V_{DS}, I_D = 250μA V_{GS} = V_{DS}, I_D = -250μA	Q1 Q2	2.0 -1.0	2.6 -1.6	4.0 -3.0	V
$\frac{\Delta V_{GS(th)}}{\Delta T_J}$	Gate to Source Threshold Voltage Temperature Coefficient	I_D = 250μA, referenced to 25°C I_D = -250μA, referenced to 25°C	Q1 Q2		-6.7 4.6	mV/°C	
$r_{DS(on)}$	Static Drain to Source On Resistance	V_{GS} = 10V, I_D = 4.3A V_{GS} = 6.0V, I_D = 4.1A V_{GS} = 10V, I_D = 4.3A, T_J = 125°C	Q1		64 70 121	80 88 152	mΩ
		V_{GS} = -10V, I_D = -2.8A V_{GS} = -4.5V, I_D = -2.6A V_{GS} = -10V, I_D = -2.8A, T_J = 125°C	Q2		153 184 259	190 224 322	
g_{FS}	Forward Transconductance	V_{DD} = 10V, I_D = 4.3A V_{DD} = -5V, I_D = -2.8A	Q1 Q2		15 6.8		S
Dynamic Characteristics							
C_{iss}	Input Capacitance	Q1 V_{DS} = 40V, V_{GS} = 0V, f = 1MHZ	Q1 Q2		600 660	800 880	pF
C_{oss}	Output Capacitance	Q2 V_{DS} = -40V, V_{GS} = 0V, f = 1MHZ	Q1 Q2		56 50	75 70	pF
C_{rss}	Reverse Transfer Capacitance		Q1 Q2		27 25	41 40	pF
R_g	Gate Resistance	f = 1MHz	Q1 Q2		1.7 7.2		Ω
Switching Characteristics							
$t_{d(on)}$	Turn-On Delay Time	Q1 V_{DD} = 40V, I_D = 4.3A, V_{GS} = 10V, R_{GEN} = 6Ω Q2 V_{DD} = -40V, I_D = -2.8A, V_{GS} = -10V, R_{GEN} = 6Ω	Q1 Q2		7 6	13 11	ns
t_r	Rise Time		Q1 Q2		2 3	10 10	ns
$t_{d(off)}$	Turn-Off Delay Time		Q1 Q2		16 25	29 40	ns
t_f	Fall Time		Q1 Q2		2 5	10 10	ns
$Q_{g(TOT)}$	Total Gate Charge	Q1 V_{GS} = 10V, V_{DD} = 40V, I_D = 4.3A Q2 V_{GS} = -10V, V_{DD} = -40V, I_D = -2.8A	Q1 Q2		13 14	18 20	nC
Q_{gs}	Gate to Source Charge		Q1 Q2		2.3 1.9		nC
Q_{gd}	Gate to Drain “Miller” Charge		Q1 Q2		3.2 2.9		nC

Electrical Characteristics T_J = 25°C unless otherwise noted

Symbol	Parameter	Test Conditions	Type	Min	Typ	Max	Units
Drain-Source Diode Characteristics							
V_{SD}	Source to Drain Diode Forward Voltage	V_{GS} = 0V, I_S = 2.6A (Note 2) V_{GS} = 0V, I_S = -2.6A (Note 2)	Q1 Q2		0.8 -0.8	1.2 -1.2	V
t_{rr}	Reverse Recovery Time	Q1 I_F = 4.3A, di/dt = 100A/s	Q1 Q2		29 30	46 48	ns
Q_{rr}	Reverse Recovery Charge	Q2 I_F = -2.8A, di/dt = 100A/s	Q1 Q2		28 30	45 48	nC

Notes:

1. $R_{\theta JA}$ is determined with the device mounted on a 1in^2 pad 2 oz copper pad on a 1.5 x 1.5 in. board of FR-4 material. $R_{\theta JC}$ is guaranteed by design while $R_{\theta CA}$ is determined by the user's board design.

Q1



a. 40°C/W when mounted on a 1 in^2 pad of 2 oz copper

Scale 1 : 1 on letter size paper

b. 96°C/W when mounted on a minimum pad of 2 oz copper

Q2



a. 40°C/W when mounted on a 1 in^2 pad of 2 oz copper

Scale 1 : 1 on letter size paper

b. 96°C/W when mounted on a minimum pad of 2 oz copper

2. Pulse Test: Pulse Width < 300μs, Duty cycle < 2.0%.

3. Starting T_J = 25°C, N-ch: L = 3mH, I_{AS} = 5A, V_{DD} = 80V, V_{GS} = 10V; P-ch: L = 3mH, I_{AS} = -6A, V_{DD} = -80V, V_{GS} = -10V.

Typical Characteristics (Q1 N-Channel) T_J = 25°C unless otherwise noted



Figure 1. On Region Characteristics



Figure 2. Normalized On-Resistance vs Drain Current and Gate Voltage



Figure 3. Normalized On Resistance vs Junction Temperature



Figure 4. On-Resistance vs Gate to Source Voltage



Figure 5. Transfer Characteristics



Figure 6. Source to Drain Diode Forward Voltage vs Source Current

Typical Characteristics (Q1 N-Channel) T_J = 25°C unless otherwise noted



Figure 7. Gate Charge Characteristics



Figure 8. Capacitance vs Drain to Source Voltage



Figure 9. Unclamped Inductive Switching Capability



Figure 10. Maximum Continuous Drain Current vs Case Temperature



Figure 11. Forward Bias Safe Operating Area



Figure 12. Single Pulse Maximum Power Dissipation

Typical Characteristics (Q1 N-Channel) T_J = 25°C unless otherwise noted



Figure 13. Transient Thermal Response Curve



Figure 14. Transient Thermal Response Curve

Typical Characteristics (Q2 P-Channel) T_J = 25°C unless otherwise noted



Figure 15. On- Region Characteristics



Figure 16. Normalized on-Resistance vs Drain Current and Gate Voltage



Figure 17. Normalized On-Resistance vs Junction Temperature



Figure 18. On-Resistance vs Gate to Source Voltage



Figure 19. Transfer Characteristics



Figure 20. Source to Drain Diode Forward Voltage vs Source Current

Typical Characteristics (Q2 P-Channel) T_J = 25°C unless otherwise noted



Figure 21. Gate Charge Characteristics



Figure 22. Capacitance vs Drain to Source Voltage



Figure 23. Unclamped Inductive Switching Capability



Figure 24. Maximum Continuous Drain Current vs Case Temperature



Figure 25. Forward Bias Safe Operating Area



Figure 26. Single Pulse Maximum Power Dissipation

Typical Characteristics (Q2 P-Channel) T_J = 25°C unless otherwise noted



Figure 27. Transient Thermal Response Curve



Figure 28. Transient Thermal Response Curve

ON Semiconductor and ON are trademarks of Semiconductor Components Industries, LLC dba ON Semiconductor or its subsidiaries in the United States and/or other countries. ON Semiconductor owns the rights to a number of patents, trademarks, copyrights, trade secrets, and other intellectual property. A listing of ON Semiconductor's product/patent coverage may be accessed at www.onsemi.com/site/pdf/Patent−Marking.pdf. ON Semiconductor reserves the right to make changes without further notice to any products herein. ON Semiconductor makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does ON Semiconductor assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. Buyer is responsible for its products and applications using ON Semiconductor products, including compliance with all laws, regulations and safety requirements or standards, regardless of any support or applications information provided by ON Semiconductor. "Typical" parameters which may be provided in ON Semiconductor data sheets and/or specifications can and do vary in different applications and actual performance may vary over time. All operating parameters, including "Typicals" must be validated for each customer application by customer's technical experts. ON Semiconductor does not convey any license under its patent rights nor the rights of others. ON Semiconductor products are not designed, intended, or authorized for use as a critical component in life support systems or any FDA Class 3 medical devices or medical devices with a same or similar classification in a foreign jurisdiction or any devices intended for implantation in the human body. Should Buyer purchase or use ON Semiconductor products for any such unintended or unauthorized application, Buyer shall indemnify and hold ON Semiconductor and its officers, employees, subsidiaries, affiliates, and distributors harmless against all claims, costs, damages, and expenses, and reasonable attorney fees arising out of, directly or indirectly, any claim of personal injury or death associated with such unintended or unauthorized use, even if such claim alleges that ON Semiconductor was negligent regarding the design or manufacture of the part. ON Semiconductor is an Equal Opportunity/Affirmative Action Employer. This literature is subject to all applicable copyright laws and is not for resale in any manner.

PUBLICATION ORDERING INFORMATION

LITERATURE FULFILLMENT:
Literature Distribution Center for ON Semiconductor
19521 E. 32nd Pkwy, Aurora, Colorado 80011 USA
Phone: 303−675−2175 or 800−344−3860 Toll Free USA/Canada
Fax: 303−675−2176 or 800−344−3867 Toll Free USA/Canada
Email: orderlit@onsemi.com

N. American Technical Support: 800−282−9855 Toll Free USA/Canada
Europe, Middle East and Africa Technical Support:
Phone: 421 33 790 2910
Japan Customer Focus Center
Phone: 81−3−5817−1050

ON Semiconductor Website: **www.onsemi.com**

Order Literature: http://www.onsemi.com/orderlit

For additional information, please contact your local Sales Representative