IXYS

Advance Technical Information

Linear L2™ Power MOSFET w/Extended FBSOA

IXTN110N20L2

V_{DSS} = 200V
I_{D25} = 100A
$R_{DS(on)}$ ≤ 24mΩ

N-Channel Enhancement Mode
Guaranteed FBSOA
Avalanche Rated



miniBLOC, SOT-227
E153432



G = Gate D = Drain
S = Source

Either Source Terminal S can be used as the Source Terminal or the Kelvin Source (Gate Return) Terminal.

Symbol	Test Conditions		Maximum Ratings	
V_{DSS}	T_J = 25°C to 150°C		200	V
V_{DGR}	T_J = 25°C to 150°C, R_{GS} = 1MΩ		200	V
V_{GSS}	Continuous		±20	V
V_{GSM}	Transient		±30	V
I_{D25}	T_C = 25°C		100	A
I_{DM}	T_C = 25°C, Pulse Width Limited by T_{JM}		275	A
I_A	T_C = 25°C		55	A
E_{AS}	T_C = 25°C		5	J
P_D	T_C = 25°C		735	W
T_J			-55 ... +150	°C
T_{JM}			150	°C
T_{stg}			-55 ... +150	°C
T_L	1.6mm (0.062 in.) from Case for 10s		300	°C
T_{SOLD}	Plastic Body for 10s		260	°C
V_{ISOL}	50/60 Hz, RMS	t = 1 Minute	2500	V~
	I_{ISOL} ≤ 1mA	t = 1 Second	3000	V~
M_d	Mounting Torque		1.5/13	Nm/lb.in.
	Terminal Connection Torque		1.3/11.5	Nm/lb.in.
Weight			30	g

Symbol	Test Conditions (T_J = 25°C, Unless Otherwise Specified)	Characteristic Values Min.	Typ.	Max.	
BV_{DSS}	V_{GS} = 0V, I_D = 1mA	200			V
$V_{GS(th)}$	V_{DS} = V_{GS}, I_D = 3mA	2.0		4.5	V
I_{GSS}	V_{GS} = ±20V, V_{DS} = 0V			±200	nA
I_{DSS}	V_{DS} = V_{DSS}, V_{GS} = 0V			50	μA
	T_J = 125°C			2.5	mA
$R_{DS(on)}$	V_{GS} = 10V, I_D = 55A, Note 1			24	mΩ

Features

- Designed for Linear Operation
- International Standard Package
- Guaranteed FBSOA at 75°C
- Avalanche Rated
- Molding Epoxy Meets UL94 V-0 Flammability Classification
- MiniBLOC with Aluminium Nitride Isolation

Applications

- Programmable Loads
- Current Regulators
- DC-DC Converters
- Battery Chargers
- DC Choppers
- Temperature and Lighting Controls

Advantages

- Easy to Mount
- Space Savings
- High Power Density

© 2009 IXYS CORPORATION, All Rights Reserved

Symbol	Test Conditions (T_J = 25°C, Unless Otherwise Specified)	Characteristic Values Min.	Typ.	Max.	
g_{fs}	V_{DS}= 10V, I_D = 55A, Note 1	55	75	95	S
C_{iss}	V_{GS} = 0V, V_{DS} = 25V, f = 1MHz		23		nF
C_{oss}			2160		pF
C_{rss}			320		pF
$t_{d(on)}$	**Resistive Switching Times**		40		ns
t_r	V_{GS} = 10V, V_{DS} = 0.5 • V_{DSS}, I_D = 55A		100		ns
$t_{d(off)}$	R_G = 1Ω (External)		33		ns
t_f			135		ns
$Q_{g(on)}$	V_{GS}= 10V, V_{DS} = 0.5 • V_{DSS}, I_D = 55A		500		nC
Q_{gs}			110		nC
Q_{gd}			182		nC
R_{thJC}				0.17	°C/W
R_{thCS}			0.05		°C/W

SOT-227B (IXTN) Outline



(M4 screws (4x) supplied)

SYM	INCHES MIN	INCHES MAX	MILLIMETERS MIN	MILLIMETERS MAX
A	1.240	1.255	31.50	31.88
B	.307	.323	7.80	8.20
C	.161	.169	4.09	4.29
D	.161	.169	4.09	4.29
E	.161	.169	4.09	4.29
F	.587	.595	14.91	15.11
G	1.186	1.193	30.12	30.30
H	1.496	1.505	38.00	38.23
J	.460	.481	11.68	12.22
K	.351	.378	8.92	9.60
L	.030	.033	0.76	0.84
M	.496	.506	12.60	12.85
N	.990	1.001	25.15	25.42
O	.078	.084	1.98	2.13
P	.195	.235	4.95	5.97
Q	1.045	1.059	26.54	26.90
R	.155	.174	3.94	4.42
S	.186	.191	4.72	4.85
T	.968	.987	24.59	25.07
U	-.002	.004	-0.05	0.1

Safe-Operating-Area Specification

Symbol	Test Conditions	Characteristic Values Min.	Typ.	Max.	
SOA	V_{DS} = 200V, I_D = 1.75A, T_C = 75°C , Tp = 3s	350			W

Source-Drain Diode

Symbol	Test Conditions (T_J = 25°C, Unless Otherwise Specified)	Characteristic Values Min.	Typ.	Max.	
I_S	V_{GS} = 0V			110	A
I_{SM}	Repetitive, Pulse Width Limited by T_{JM}			440	A
V_{SD}	I_F = 55A, V_{GS} = 0V, Note 1			1.35	V
t_{rr}	I_F = 55A, -di/dt = 100A/µs,		420		ns
I_{RM}	V_R = 100V, V_{GS} = 0V		39		A
Q_{RM}			8.3		µC

Note 1. Pulse Test, t ≤ 300µs; Duty Cycle, d ≤ 2%.

ADVANCE TECHNICAL INFORMATION

The product presented herein is under development. The Technical Specifications offered are derived from a subjective evaluation of the design, based upon prior knowledge and experience, and constitute a "considered reflection" of the anticipated result. IXYS reserves the right to change limits, test conditions, and dimensions without notice.

IXYS Reserves the Right to Change Limits, Test Conditions, and Dimensions.

IXYS MOSFETs and IGBTs are covered by one or more of the following U.S. patents: 4,835,592 4,850,072 4,881,106 4,931,844 5,017,508 5,034,796 5,049,961 5,063,307 5,187,117 5,237,481 5,381,025 5,486,715 6,162,665 6,259,123 B1 6,306,728 B1 6,404,065 B1 6,534,343 6,583,505 6,683,344 6,710,405 B2 6,710,463 6,727,585 6,759,692 6,771,478 B2 7,005,734 B2 7,063,975 B2 7,071,537 7,157,338B2

Fig. 1. Output Characteristics @ T_J = 25ºC



Fig. 2. Extended Output Characteristics @ T_J = 25ºC



Fig. 3. Output Characteristics @ T_J = 125ºC



Fig. 4. $R_{DS(on)}$ Normalized to I_D = 55A Value vs. Junction Temperature



Fig. 5. $R_{DS(on)}$ Normalized to I_D = 55A Value vs. Drain Current



Fig. 6. Maximum Drain Current vs. Case Temperature



© 2009 IXYS CORPORATION, All Rights Reserved

Fig. 7. Input Admittance



Fig. 8. Transconductance



Fig. 9. Forward Voltage Drop of Intrinsic Diode



Fig. 10. Gate Charge



Fig. 11. Capacitance



Fig. 12. Maximum Transient Thermal Impedance



IXYS Reserves the Right to Change Limits, Test Conditions, and Dimensions.

Fig. 13. Forward-Bias Safe Operating Area @ T_C = 25ºC



Fig. 14. Forward-Bias Safe Operating Area @ T_C = 75ºC



© 2009 IXYS CORPORATION, All Rights Reserved

Disclaimer Notice - Information furnished is believed to be accurate and reliable. However, users should independently evaluate the suitability of and test each product selected for their own applications. Littelfuse products are not designed for, and may not be used in, all applications. Read complete Disclaimer Notice at www.littelfuse.com/disclaimer-electronics.