

To our customers,

Old Company Name in Catalogs and Other Documents

On April 1st, 2010, NEC Electronics Corporation merged with Renesas Technology Corporation, and Renesas Electronics Corporation took over all the business of both companies. Therefore, although the old company name remains in this document, it is a valid Renesas Electronics document. We appreciate your understanding.

Renesas Electronics website: <http://www.renesas.com>

April 1st, 2010
Renesas Electronics Corporation

Issued by: Renesas Electronics Corporation (<http://www.renesas.com>)

Send any inquiries to <http://www.renesas.com/inquiry>.

Notice

1. All information included in this document is current as of the date this document is issued. Such information, however, is subject to change without any prior notice. Before purchasing or using any Renesas Electronics products listed herein, please confirm the latest product information with a Renesas Electronics sales office. Also, please pay regular and careful attention to additional and different information to be disclosed by Renesas Electronics such as that disclosed through our website.
2. Renesas Electronics does not assume any liability for infringement of patents, copyrights, or other intellectual property rights of third parties by or arising from the use of Renesas Electronics products or technical information described in this document. No license, express, implied or otherwise, is granted hereby under any patents, copyrights or other intellectual property rights of Renesas Electronics or others.
3. You should not alter, modify, copy, or otherwise misappropriate any Renesas Electronics product, whether in whole or in part.
4. Descriptions of circuits, software and other related information in this document are provided only to illustrate the operation of semiconductor products and application examples. You are fully responsible for the incorporation of these circuits, software, and information in the design of your equipment. Renesas Electronics assumes no responsibility for any losses incurred by you or third parties arising from the use of these circuits, software, or information.
5. When exporting the products or technology described in this document, you should comply with the applicable export control laws and regulations and follow the procedures required by such laws and regulations. You should not use Renesas Electronics products or the technology described in this document for any purpose relating to military applications or use by the military, including but not limited to the development of weapons of mass destruction. Renesas Electronics products and technology may not be used for or incorporated into any products or systems whose manufacture, use, or sale is prohibited under any applicable domestic or foreign laws or regulations.
6. Renesas Electronics has used reasonable care in preparing the information included in this document, but Renesas Electronics does not warrant that such information is error free. Renesas Electronics assumes no liability whatsoever for any damages incurred by you resulting from errors in or omissions from the information included herein.
7. Renesas Electronics products are classified according to the following three quality grades: “Standard”, “High Quality”, and “Specific”. The recommended applications for each Renesas Electronics product depends on the product’s quality grade, as indicated below. You must check the quality grade of each Renesas Electronics product before using it in a particular application. You may not use any Renesas Electronics product for any application categorized as “Specific” without the prior written consent of Renesas Electronics. Further, you may not use any Renesas Electronics product for any application for which it is not intended without the prior written consent of Renesas Electronics. Renesas Electronics shall not be in any way liable for any damages or losses incurred by you or third parties arising from the use of any Renesas Electronics product for an application categorized as “Specific” or for which the product is not intended where you have failed to obtain the prior written consent of Renesas Electronics. The quality grade of each Renesas Electronics product is “Standard” unless otherwise expressly specified in a Renesas Electronics data sheets or data books, etc.
 - “Standard”: Computers; office equipment; communications equipment; test and measurement equipment; audio and visual equipment; home electronic appliances; machine tools; personal electronic equipment; and industrial robots.
 - “High Quality”: Transportation equipment (automobiles, trains, ships, etc.); traffic control systems; anti-disaster systems; anti-crime systems; safety equipment; and medical equipment not specifically designed for life support.
 - “Specific”: Aircraft; aerospace equipment; submersible repeaters; nuclear reactor control systems; medical equipment or systems for life support (e.g. artificial life support devices or systems), surgical implantations, or healthcare intervention (e.g. excision, etc.), and any other applications or purposes that pose a direct threat to human life.
8. You should use the Renesas Electronics products described in this document within the range specified by Renesas Electronics, especially with respect to the maximum rating, operating supply voltage range, movement power voltage range, heat radiation characteristics, installation and other product characteristics. Renesas Electronics shall have no liability for malfunctions or damages arising out of the use of Renesas Electronics products beyond such specified ranges.
9. Although Renesas Electronics endeavors to improve the quality and reliability of its products, semiconductor products have specific characteristics such as the occurrence of failure at a certain rate and malfunctions under certain use conditions. Further, Renesas Electronics products are not subject to radiation resistance design. Please be sure to implement safety measures to guard them against the possibility of physical injury, and injury or damage caused by fire in the event of the failure of a Renesas Electronics product, such as safety design for hardware and software including but not limited to redundancy, fire control and malfunction prevention, appropriate treatment for aging degradation or any other appropriate measures. Because the evaluation of microcomputer software alone is very difficult, please evaluate the safety of the final products or system manufactured by you.
10. Please contact a Renesas Electronics sales office for details as to environmental matters such as the environmental compatibility of each Renesas Electronics product. Please use Renesas Electronics products in compliance with all applicable laws and regulations that regulate the inclusion or use of controlled substances, including without limitation, the EU RoHS Directive. Renesas Electronics assumes no liability for damages or losses occurring as a result of your noncompliance with applicable laws and regulations.
11. This document may not be reproduced or duplicated, in any form, in whole or in part, without prior written consent of Renesas Electronics.
12. Please contact a Renesas Electronics sales office if you have any questions regarding the information contained in this document or Renesas Electronics products, or if you have any other inquiries.


(Note 1) “Renesas Electronics” as used in this document means Renesas Electronics Corporation and also includes its majority-owned subsidiaries.

(Note 2) “Renesas Electronics product(s)” means any product developed or manufactured by or for Renesas Electronics.

AC16DGM to AC16FGM

16 A MOLD TRIAC

PACKAGE DIMENSIONS in millimeters



The AC16DGM to AC16FGM are all diffused mold type TRIAC granted RMS On-state current 16 Amps, with rated voltages up to 600 Volts.

FEATURES

- 150 A Surge Current
- TO-220AB mold package
- Low cost

APPLICATIONS

Motor speed control,
Lamp dimmer, Temperature controllers,
Various solid state switches, etc.

MAXIMUM RATINGS

ITEM	SYMBOL	AC16DGM	AC16EGM	AC16FGM	UNIT	NOTE
Repetitive Peak-off Voltage	V_{DRM}	400	500	600	V	
Non-Repetitive Peak-off Voltage	V_{DSM}	500	600	700	V	
RMS On-state Current	$I_T(RMS)$	16 ($T_c = 100^\circ C$)			A	See Fig. 11, 12
Surge On-state Current	I_{TSM}	150 (50 Hz Non-repetitive)			A	See Fig. 2
Fusing Current	$\int i^2 T^2 dt$	100			A ² S	
Peak Gate Power Dissipation	P_{GM}	5			W	
Average Gate Power Dissipation	$P_{G(AV)}$	0.5			W	
Peak Gate Current	I_{GM}	± 3			A	
Junction Temperature	T_j	-40 to +125			$^\circ C$	
Storage Temperature	T_{stg}	-40 to +125			$^\circ C$	

ITEM		SYMBOL	TEST CONDITIONS		MIN.	TYP.	MAX.	UNIT	NOTE
Peak Off-State Current		I_{DRM}	$V_{\text{DM}} = V_{\text{DRM}}$	$T_{\text{J}} = 25\text{ }^{\circ}\text{C}$	—	—	0.1	mA	—
				$T = 125\text{ }^{\circ}\text{C}$	—	—	2		
On-State Voltage		V_{TM}	$I_{\text{TM}} = 25\text{ A}$		—	—	1.4	V	See Fig. 1
Critical Rate of Rise of Off-state Voltage		dv/dt	$T_{\text{J}} = 125\text{ }^{\circ}\text{C}$ $V_{\text{DM}} = \frac{2}{3} V_{\text{DRM}}$		—	100	—	V/ μs	—
DC Gate Trigger Current	I	I_{GT}	$V_{\text{DM}} = 12\text{ V}$ $R_{\text{L}} = 30\text{ }\Omega$	T_2+ , G+	—	—	30	mA	See Fig. 3, 4, 5, 7
	II			T_2- , G+	—	—	80		
	III			T_2- , G—	—	—	30		
	IV			T_2+ , G—	—	—	30		
DC Gate Trigger Voltage	I	V_{GT}	$V_{\text{DM}} = 12\text{ V}$ $R_{\text{L}} = 30\text{ }\Omega$	T_2+ , G+	—	—	1.5	V	See Fig. 3, 4, 6, 8
	II			T_2- , G+	—	—	2.0		
	III			T_2- , G—	—	—	1.5		
	IV			T_2+ , G—	—	—	1.5		
Gate Non-Trigger Voltage		V_{GD}	$T_{\text{J}} = 125\text{ }^{\circ}\text{C}$ $V_{\text{DM}} = \frac{1}{2} V_{\text{DRM}}$		0.3	—	—	V	—
DC Holding Current		I_{H}	$V_{\text{D}} = 24\text{ V}$		—	30	—	mA	
Critical Rate of Rise of Commutating Off-State Voltage		$(dv/dt)_{\text{c}}$	$T_{\text{J}} = 125\text{ }^{\circ}\text{C}$, $I_{\text{TM}} = 22\text{ A}$ $(di_{\text{T}}/dt)_{\text{c}} = -8\text{ A/ms}$ $V_{\text{D}} = 400\text{ V}$		10	—	—	V/ μs	
Thermal Resistance		$R_{\text{th(j-c)}}$	Junction-to-Case		—	—	1.5	$^{\circ}\text{C/W}$	See Fig. 13

Fig. 1 $i_T - v_T$ CHARACTERISTIC




Fig. 2 I_{TSM} RATING




Fig. 3 $V_G - I_G$ RATING




Fig. 4 $V_{GT} - I_{GT}$ CHARACTERISTIC




Fig. 5 $I_{GT} - T_a$ TYPICAL DISTRIBUTION




Fig. 6 $V_{GT} - T_a$ TYPICAL DISTRIBUTION











Fig. 7 $i_{GT} - \tau$ TYPICAL DISTRIBUTIONFig. 8 $v_{GT} - \tau$ TYPICAL DISTRIBUTIONFig. 9 $I_H - T_a$ CHARACTERISTICFig. 10 $P_{T(AV)} - I_{T(RMS)}$ CHARACTERISTICFig. 11 $T_c - I_{T(RMS)}$ RATINGFig. 12 $T_a - I_{T(RMS)}$ RATING

Fig. 13 Z_{th} CHARACTERISTIC



NEC Corporation

INTERNATIONAL ELECTRON DEVICES DIV.

SUMITOMO MITA Building, 37-8,
Shiba Gochome, Minato-ku, Tokyo 108, Japan
Tel: Tokyo 456-3111
Telex Address: NECTOK J22686
Cable Address: NEC TOKYO