TSM4424

20V N-Channel MOSFET

SOP-8



Pin Definition:

1. Source	8. Drain
2. Source	7. Drain
3. Source	6. Drain
4. Gate	5. Drain

Key Parameter Performance

Parameter	Value	Unit
V_{DS}	20	V
$R_{DS(on)}$ (max)	30	mΩ
Q_g	11.2	nC

Features

- Advance Trench Process Technology
- High Density Cell Design for Ultra Low On-resistance

Application

- Specially Designed for Li-on Battery Packs
- Battery Switch Application

Block Diagram



N-Channel MOSFET

Ordering Information

Part No.	Package	Packing
TSM4424CS RLG	SOP-8	2.5Kpcs / 13” Reel
TSM4424CS RVG	SOP-8	3Kpcs / 13” Reel

Note: “G” denotes for Halogen- and Antimony-free as those which contain <900ppm bromine, <900ppm chlorine (<1500ppm total Br + Cl) and <1000ppm antimony compounds

Absolute Maximum Ratings (T_C = 25°C, unless otherwise noted)

Parameter		Symbol	Limit	Unit
Drain-Source Voltage		V_{DS}	20	V
Gate-Source Voltage		V_{GS}	±8	V
Continuous Drain Current		I_D	8	A
Pulsed Drain Current (Note 1)		I_{DM}	30	A
Continuous Source Current (Diode Conduction)		I_S	2.2	A
Maximum Power Dissipation	Ta = 25°C	P_D	2.5	W
	Ta = 75°C		1.3	
Operating Junction Temperature		T_J	+150	°C
Operating Junction and Storage Temperature Range		T_J, T_{STG}	-55 to +150	°C

Thermal Performance

Parameter	Symbol	Limit	Unit
Thermal Resistance Junction to Foot	$R_{\Theta JF}$	25	°C/W
Thermal Resistance Junction to Ambient	$R_{\Theta JA}$	52.5	°C/W

TSM4424

20V N-Channel MOSFET

Electrical Specifications

Parameter	Conditions	Symbol	Min	Typ	Max	Unit
Static(Note 2)						
Drain-Source Breakdown Voltage	V_{GS} = 0V, I_D = 250uA	BV_{DSS}	20	--	--	V
Gate Threshold Voltage	V_{DS} = V_{GS}, I_D = 250uA	$V_{GS(TH)}$	--	0.65	1	V
Gate Body Leakage	V_{GS} = ±8V, V_{DS} = 0V	I_{GSS}	--	--	±100	nA
Zero Gate Voltage Drain Current	V_{DS} = 20V, V_{GS} = 0V	I_{DSS}	--	--	1.0	uA
On-State Drain Current	V_{DS} =5V, V_{GS} = 4.5V	$I_{D(ON)}$	30	--	--	A
Drain-Source On-State Resistance	V_{GS} = 4.5V, I_D = 4.5A	$R_{DS(ON)}$	--	23	30	mΩ
	V_{GS} = 2.5V, I_D = 3.5A		--	25	35	
	V_{GS} = 1.8V, I_D = 2.0A		--	35	45	
Forward Transconductance	V_{DS} = 10V, I_D = 6A	g_{fs}	--	40	--	S
Diode Forward Voltage	I_S = 1.7A, V_{GS} = 0V	V_{SD}	--	0.8	1.2	V
Dynamic(Note 3)						
Total Gate Charge	V_{DS} = 10V, I_D = 4.5A, V_{GS} = 4.5V	Q_g	--	11.2	14	nC
Gate-Source Charge		Q_{gs}	--	1.4	--	
Gate-Drain Charge		Q_{gd}	--	2.2	--	
Input Capacitance	V_{DS} = 10V, V_{GS} = 0V, f = 1.0MHz	C_{iss}	--	500	--	pF
Output Capacitance		C_{oss}	--	300	--	
Reverse Transfer Capacitance		C_{rss}	--	140	--	
Switching(Note 4)						
Turn-On Delay Time	V_{DD} = 10V, R_L = 10Ω, I_D = 1A, V_{GEN} = 4.5V, R_G = 6Ω	$t_{d(on)}$	--	15	25	ns
Turn-On Rise Time		t_r	--	30	60	
Turn-Off Delay Time		$t_{d(off)}$	--	35	70	
Turn-Off Fall Time		t_f	--	15	45	

Notes:

1. Pulse width limited by the maximum junction temperature
2. Pulse test: PW ≤ 300μs, duty cycle ≤ 2%
3. For DESIGN AID ONLY, not subject to production testing.
4. Switching time is essentially independent of operating temperature.



Switching Test Circuit



Switchin Waveforms

Electrical Characteristics Curve

Output Characteristics



Transfer Characteristics



On-Resistance vs. Drain Current



Gate Charge



On-Resistance vs. Junction Temperature



Source-Drain Diode Forward Voltage



Electrical Characteristics Curve

On-Resistance vs. Gate-Source Voltage



Threshold Voltage



Safety Operation Area



Normalized Thermal Transient Impedance, Junction-to-Ambient



SOP-8 Mechanical Drawing



Unit: Millimeters

Marking Diagram

Y = Year Code
M = Month Code for Halogen Free Product

O	=Jan	**P**	=Feb	**Q**	=Mar	**R**	=Apr
S	=May	**T**	=Jun	**U**	=Jul	**V**	=Aug
W	=Sep	**X**	=Oct	**Y**	=Nov	**Z**	=Dec

L = Lot Code

Notice

Specifications of the products displayed herein are subject to change without notice. TSC or anyone on its behalf, assumes no responsibility or liability for any errors or inaccuracies.

Information contained herein is intended to provide a product description only. No license, express or implied, to any intellectual property rights is granted by this document. Except as provided in TSC's terms and conditions of sale for such products, TSC assumes no liability whatsoever, and disclaims any express or implied warranty, relating to sale and/or use of TSC products including liability or warranties relating to fitness for a particular purpose, merchantability, or infringement of any patent, copyright, or other intellectual property right.

The products shown herein are not designed for use in medical, life-saving, or life-sustaining applications. Customers using or selling these products for use in such applications do so at their own risk and agree to fully indemnify TSC for any damages resulting from such improper use or sale.