


EPC2052 – Enhancement Mode Power Transistor


 $V_{DS}, 100\text{ V}$
 $R_{DS(on)}, 13.5\text{ m}\Omega$
 $I_D, 8.2\text{ A}$


Revised September 26, 2022

Gallium Nitride's exceptionally high electron mobility and low temperature coefficient allows very low $R_{DS(on)}$, while its lateral device structure and majority carrier diode provide exceptionally low Q_G and zero Q_{RR} . The end result is a device that can handle tasks where very high switching frequency, and low on-time are beneficial as well as those where on-state losses dominate.

Questions:

Ask a GaN Expert



Die Size: 1.5 x 1.5 mm

EPC2052 eGaN® FETs are supplied in passivated die form with solder bumps.

Applications

- 48 V Servers
- Lidar/Pulsed Power
- Isolated Power Supplies
- Point of Load Converters
- Class D Audio
- LED Lighting
- Low Inductance Motor Drive

Benefits

- Higher Switching Frequency – Lower switching losses and lower drive power
- Higher Efficiency – Lower conduction and switching losses, zero reverse recovery losses
- Ultra Small Footprint - Higher power density

Scan QR code or click link below for more information including reliability reports, device models, demo boards!


<https://l.ead.me/EPC2052>

Maximum Ratings

PARAMETER		VALUE	UNIT
V_{DS}	Drain-to-Source Voltage (Continuous)	100	V
	Drain-to-Source Voltage (up to 10,000 5 ms pulses at 150°C)	120	
I_D	Continuous ($T_A = 25^\circ\text{C}$)	8.2	A
	Pulsed (25°C , $T_{PULSE} = 300\text{ }\mu\text{s}$)	74	
V_{GS}	Gate-to-Source Voltage	6	V
	Gate-to-Source Voltage	-4	
T_J	Operating Temperature	-40 to 150	$^\circ\text{C}$
T_{STG}	Storage Temperature	-40 to 150	

Thermal Characteristics

PARAMETER		TYP	UNIT
$R_{\theta JC}$	Thermal Resistance, Junction-to-Case	2	$^\circ\text{C/W}$
$R_{\theta JB}$	Thermal Resistance, Junction-to-Board	15	
$R_{\theta JA}$	Thermal Resistance, Junction-to-Ambient (Note 1)	74	

Note 1: $R_{\theta JA}$ is determined with the device mounted on one square inch of copper pad, single layer 2 oz copper on FR4 board. See https://epc-co.com/epc/documents/product-training/Appnote_Thermal_Performance_of_eGaN_FETs.pdf for details.

Static Characteristics ($T_J = 25^\circ\text{C}$ unless otherwise stated)

PARAMETER		TEST CONDITIONS	MIN	TYP	MAX	UNIT
BV_{DSS}	Drain-to-Source Voltage	$V_{GS} = 0\text{ V}$, $I_D = 0.2\text{ mA}$	100			V
I_{DSS}	Drain-Source Leakage	$V_{DS} = 80\text{ V}$, $V_{GS} = 0\text{ V}$, $T_J = 25^\circ\text{C}$		0.02	0.15	mA
I_{GSS}	Gate-to-Source Forward Leakage	$V_{GS} = 5\text{ V}$, $T_J = 25^\circ\text{C}$		0.01	1.8	mA
		$V_{GS} = 5\text{ V}$, $T_J = 125^\circ\text{C}$		0.2	4	mA
	Gate-to-Source Reverse Leakage [#]	$V_{GS} = -4\text{ V}$, $T_J = 25^\circ\text{C}$		0.01	0.18	mA
$V_{GS(TH)}$	Gate Threshold Voltage	$V_{DS} = V_{GS}$, $I_D = 3\text{ mA}$	0.8	1.4	2.5	V
$R_{DS(on)}$	Drain-Source On Resistance	$V_{GS} = 5\text{ V}$, $I_D = 11\text{ A}$		10	13.5	m Ω
V_{SD}	Source-Drain Forward Voltage [#]	$I_S = 0.5\text{ A}$, $V_{GS} = 0\text{ V}$		2.0		V

[#] Defined by design. Not subject to production test.

Dynamic Characteristics[#] ($T_J = 25^\circ\text{C}$ unless otherwise stated)

PARAMETER		TEST CONDITIONS	MIN	TYP	MAX	UNIT
C_{ISS}	Input Capacitance	$V_{DS} = 50\text{ V}, V_{GS} = 0\text{ V}$		441	584	pF
C_{RSS}	Reverse Transfer Capacitance			3.2		
C_{OSS}	Output Capacitance			195	293	
$C_{OSS(ER)}$	Effective Output Capacitance, Energy Related (Note 2)	$V_{DS} = 0\text{ to }50\text{ V}, V_{GS} = 0\text{ V}$		227		
$C_{OSS(TR)}$	Effective Output Capacitance, Time Related (Note 3)			274		
R_G	Gate Resistance			0.7		Ω
Q_G	Total Gate Charge	$V_{DS} = 50\text{ V}, V_{GS} = 5\text{ V}, I_D = 11\text{ A}$		3.5	4.5	nC
Q_{GS}	Gate to Source Charge	$V_{DS} = 50\text{ V}, I_D = 11\text{ A}$		1.5		
Q_{GD}	Gate to Drain Charge			0.5		
$Q_{G(TH)}$	Gate Charge at Threshold			1.0		
Q_{OSS}	Output Charge	$V_{GS} = 0\text{ V}, V_{DS} = 50\text{ V}$		13	20	
Q_{RR}	Source-Drain Recovery Charge			0		

[#] Defined by design. Not subject to production test.

All measurements were done with substrate connected to source.

Note 2: $C_{OSS(ER)}$ is a fixed capacitance that gives the same stored energy as C_{OSS} while V_{DS} is rising from 0 to 50% BV_{DSS} .

Note 3: $C_{OSS(TR)}$ is a fixed capacitance that gives the same charging time as C_{OSS} while V_{DS} is rising from 0 to 50% BV_{DSS} .


Figure 1: Typical Output Characteristics at 25°C 

Figure 2: Typical Transfer Characteristics




Figure 3: Typical $R_{DS(on)}$ vs. V_{GS} for Various CurrentsFigure 4: Typical $R_{DS(on)}$ vs. V_{GS} for Various Temperatures

Figure 5a: Typical Capacitance (Linear Scale)




Figure 5b: Typical Capacitance (Log Scale)



Figure 6: Typical Output Charge and C_{OSS} Stored Energy

Figure 7: Typical Gate Charge




Figure 8: Typical Reverse Drain-Source Characteristics





Figure 9: Typical Normalized On-State Resistance vs. Temp.



Negative gate drive voltage increases the reverse drain-source voltage.
EPC recommends 0V for OFF

Figure 10: Typical Normalized Threshold Voltage vs. Temp.




Figure 11: Typical Transient Thermal Response Curves






Figure 12: Safe Operating Area



TAPE AND REEL CONFIGURATION


4mm pitch, 8mm wide tape on 7" reel



Dimension (mm)	EPC2052 (note 1)		
	target	min	max
a	8.00	7.90	8.30
b	1.75	1.65	1.85
c (see note)	3.50	3.45	3.55
d	4.00	3.90	4.10
e	4.00	3.90	4.10
f (see note)	2.00	1.95	2.05
g	1.5	1.5	1.6

Note 1: MSL 1 (moisture sensitivity level 1) classified according to IPC/JEDEC industry standard.
 Note 2: Pocket position is relative to the sprocket hole measured as true position of the pocket, not the pocket hole.


DIE MARKINGS



Part Number	Laser Markings		
	Part # Marking Line 1	Lot_Date Code Marking line 2	Lot_Date Code Marking Line 3
EPC2052	2052	YYYY	ZZZZ

DIE OUTLINE

Solder Bump View




DIM	MICROMETERS		
	MIN	Nominal	MAX
A	1470	1500	1530
B	1470	1500	1530
C		450	
D		500	
E	238	264	290

Pad 1 is Gate;

Pads 2, 3, 7, 8, 9 are Source;

Pads 4, 5, 6 are Drain.

RECOMMENDED LAND PATTERN(units in μm)

DIM	MICROMETERS
A	1500
B	1500
C	450
D	500
E	230


Pad 1 is Gate;

Pads 2, 3, 7, 8, 9 are Source;

Pads 4, 5, 6 are Drain.

RECOMMENDED STENCIL DRAWING(measurements in μm)

Additional assembly resources available at

<https://epc-co.com/epc/design-support>

DIM	MICROMETERS
A	1500
B	1500
C	450
D	500
F	300
G	250

Pad 1 is Gate;

Pads 2, 3, 7, 8, 9 are Source;

Pads 4, 5, 6 are Drain.

Recommended stencil should be 4 mil (100 μm) thick, must be laser cut, opening per drawing.

The corner has a radius of R60. Intended for use with SAC305 Type 4 solder, reference 88.5% metals content.

Efficient Power Conversion Corporation (EPC) reserves the right to make changes without further notice to any products herein to improve reliability, function or design. EPC does not assume any liability arising out of the application or use of any product or circuit described herein; neither does it convey any license under its patent rights, nor the rights of others.

eGaN® is a registered trademark of Efficient Power Conversion Corporation.

EPC Patent Listing: <https://epc-co.com/epc/about-epc/patents>

Information subject to change without notice.