


PRESSURE TRANSDUCERS


P-2000



FEATURES

- Compact and light weight
- For non-corrosive gases
- Dual in line package
- Pressure range ~9.81, ~981 kPa {~0.1, ~10 kgf/cm²}

INTERNAL STRUCTURE (BN type)



	Part name	Material
①	Housing	LCP (Liquid crystal polymer)
②	Cover	Aluminum
③	Sensor chip	Silicone
④	Chip resistor (compensatory resistor)	Ceramic
⑤	Terminal pin	Phosphor bronze + Au-plated

MODEL NUMBER DESIGNATION

P-2000 - 501 G - 15 - BN

Series name

Rated pressure range

101 : 0 ~ 9.81 kPa {0 ~ 0.1 kgf/cm²}
 501 : 0 ~ 49.0 kPa {0 ~ 0.5 kgf/cm²}
 102 : 0 ~ 98.1 kPa {0 ~ 1 kgf/cm²}
 352 : 0 ~ 343 kPa {0 ~ 3.5 kgf/cm²}
 502 : 0 ~ 490 kPa {0 ~ 5 kgf/cm²}
 702 : 0 ~ 686 kPa {0 ~ 7 kgf/cm²}
 103 : 0 ~ 981 kPa {0 ~ 10 kgf/cm²}

Terminal direction

AN : Same direction as the pressure port
 BN : Opposite direction to the pressure port

Thermal error

15 : ± 0.15 % (± 0.12 %) F.S./°C

Pressure reference

G : Gauge

LIST OF MODEL NUMBERS

Terminal direction	Rated pressure range kPa {kgf/cm ² }	0 ~ 9.81 {0 ~ 0.1}	0 ~ 49.0 {0 ~ 0.5}	0 ~ 98.1 {0 ~ 1}	0 ~ 343 {0 ~ 3.5}	0 ~ 490 {0 ~ 5}	0 ~ 686 {0 ~ 7}	0 ~ 981 {0 ~ 10}
AN		⌚ P-2000-101G-15-AN	⌚ P-2000-501G-15-AN	⌚ P-2000-102G-15-AN	⌚ P-2000-352G-15-AN	⌚ P-2000-502G-15-AN	⌚ P-2000-702G-15-AN	⌚ P-2000-103G-15-AN
BN		P-2000-101G-15-BN	P-2000-501G-15-BN	P-2000-102G-15-BN	P-2000-352G-15-BN	P-2000-502G-15-BN	P-2000-702G-15-BN	P-2000-103G-15-BN

※ Verify the above model numbers when placing orders.
 The AN version, marked ⌚ is manufactured upon receipt of order basis.

P-2000

PRESSURE TRANSDUCERS

STANDARD SPECIFICATIONS

● Unless otherwise specified, the specs are defined at an ambient temperature of 25±5 °C and excitation current of 1.5 mA DC.

Item		Model number	P-2000						
			101G	501G	102G	352G	502G	702G	103G
General specifications	Pressure reference		Gauge						
	Rated pressure range kPa {kgf/cm ² }		9.81 {0.1}	49.0 {0.5}	98.1 {1.0}	343 {3.5}	490 {5}	686 {7}	981 {10.0}
	Maximum pressure kPa {kgf/cm ² }		19.6 {0.2}	98.1 {1.0}	196 {2.0}	686 {7.0}	981 {10}	1373 {14}	1471 {15.0}
	Break-down pressure kPa {kgf/cm ² }		49.0 {0.5}	245 {2.5}	490 {5}	1030 {10.5}	1471 {15}	1961 {20}	1961 {20}
	Operating temp. range °C		- 20 ~ 80						
	Compensated temp. range °C		0 ~ 50						
	Operating humidity %RH		35 ~ 85 (No condensation)						
	Storage temp. °C		- 20 ~ 80 (Atmospheric pressure, humidity 65 %RH maximum)						
	Bridge resistance Ω		3300 ± 30 %						
	Pressure medium		Non-corrosive gases						
	Insulation resistance MΩ minimum		100 (500 VDC)						
	Dielectric strength		500 V AC, 60 s(Leakage current 1 mA maximum)						
	Pressure port mm		φ 3.2						
	Net weight g		Approx. 1						
Power	Excitation current mA DC		1.5 (Constant current)						
Analog output	Offset voltage mV		± 20	± 15					
	Span voltage mV		50 ± 20	90 ± 30					
	Linearity/Hysteresis %F.S.		± 0.3						
	Thermal error (Reference temp.: 25 °C)	ZERO %F.S./°C	± 0.15	± 0.12					
		SPAN %F.S./°C	± 0.05	± 0.04					
Response ms		Approx. 1							

ENVIRONMENTAL CHARACTERISTICS

Test item	Test conditions (At 25 ± 5 °C)	Permissible change
Vibration	10 ~ 500 Hz, 1.5 mm maximum/98.1 m/s ² , 3 directions for 2 hours each	Offset voltage/Span voltage: ±1 %F.S. maximum each
Shock	981 m/s ² , 3 directions for 3 times each	
Pressure cycling	0 ~ Rated pressure, 10 ⁶ cycles	
Moisture resistance	40 °C, 90 ~ 95 %RH, 240 hrs.	


※ P-2000 series can be operated at the vacuum pressure.

P-2000


PRESSURE TRANSDUCERS

OUTLINE DIMENSIONS

● BN type




● AN type



INTERNAL ELECTRICAL SCHEMATICS

TERMINAL NUMBER



R : Built-in chip resistor for temp. compensation

Pin	Connection
1	Output $\ominus$
2	Input $\oplus$
3	Input $\ominus$
4	Output $\oplus$
5	Input $\ominus$
6	Input $\oplus$